

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
5 June 2003 (05.06.2003)

PCT

(10) International Publication Number  
**WO 03/045179 A2**

(51) International Patent Classification<sup>7</sup>: A43B 7/22, 13/18

Gordon, A. [CA/US]; 7660 S.W. Lantana Court, Beaverton, OR 97008 (US).

(21) International Application Number: PCT/US02/35837

(74) Agent: NIEGOWSKI, James, A.; Banner & Witcoff, Ltd., 1001 G Street, N.W., Eleventh Floor, Washington, DC 20001-4597 (US).

(22) International Filing Date:

8 November 2002 (08.11.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

09/990,100 21 November 2001 (21.11.2001) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for JP, KR only*): NIKE, INC. [US/US]; One Bowerman Drive, Beaverton, OR 97005-6453 (US).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except JP, KR, US*): NIKE INTERNATIONAL LTD. [GB/US]; One Bowerman Drive, Beaverton, OR 97005-6453 (US).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): GREENE, Pamela, S. [US/US]; 6120 S.W. 41 Avenue, Portland, OR 97229 (US). HOFFER, Kevin, W. [US/US]; 3205 N.E. 64 Avenue, Portland, OR 97213 (US). LOZANO, Sergio, G. [US/US]; 15845 S.W. Cardinal Loop, Beaverton, OR 97007 (US). MARTINDALE, Michael [US/US]; 2417 N.E. 32 Avenue, Portland, OR 97212 (US). VALIANT,

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FOOTWEAR WITH REMOVABLE FOOT-SUPPORTING MEMBER

(57) Abstract: An article of footwear is disclosed having an upper, a foot-supporting member, and a sole structure. The foot-supporting member includes a heel region located at a greater elevation than a forefoot region, thereby defining a recess under the heel region. The sole structure includes a midsole that forms a protrusion on the interior of the footwear. The protrusion mates with the recess to provide support for the heel region. The foot-supporting member may also incorporate pronation control characteristics, including a downward cant from a medial to a lateral side of the foot-supporting member and a region of reduced support generally underlying the first metatarsal. To further reduce the rate of pronation, the sole structure includes a region in the rear-lateral corner that is more compressible than other areas of the sole structure.

WO 03/045179 A2

# FOOTWEAR WITH REMOVABLE FOOT-SUPPORTING MEMBER

## BACKGROUND OF THE INVENTION

### Field of the Invention

The present invention relates to footwear. The invention concerns, more particularly, an article of footwear having a removable foot-supporting member.

### Description of Background Art

One objective of modern athletic footwear design is to minimize weight while maximizing comfort, stability, and durability. In order to meet this goal, designers utilize a broad range of materials, shoe components, and shoe-making methods. The basic design of conventional athletic footwear, however, remains largely uniform and includes two primary elements, an upper and a sole structure. The upper may be formed of leather, synthetic materials, or a combination thereof and comfortably receives the foot while providing ventilation and protection from the elements. The sole structure includes multiple layers that are conventionally referred to as an insole, midsole, and outsole. The insole is a thin, padded member located adjacent to the foot that improves overall comfort of the footwear. In many articles of footwear, the insole is removable and may be replaced. The midsole forms the middle layer of the sole and often incorporate a resilient foam material, such as polyurethane or ethyl vinyl acetate, that attenuates shock and absorbs energy when the footwear is compressed against the ground. Unlike the insole, midsoles are integrally-formed with the footwear and may not be replaced or modified by a wearer. The outsole is fashioned from a durable, wear resistant material, such as carbon-black rubber compound, and typically includes a textured lower surface to improve

traction. A disadvantage relating to the laminar design of conventional sole structures is that the overall flexibility of the sole structures are decreased, particularly in the forefoot.

Some modern footwear designs depart from conventional designs by replacing a majority of the midsole with a removable sockliner. Footwear of this type includes an upper, a sockliner, a thin midsole, and an outsole. The sockliner, therefore, functions as the primary shock attenuation and energy absorbing element in both the heel and forefoot regions of the footwear. Although this design provides greater flexibility in the forefoot area than conventional laminar designs, the relatively large thickness of the sockliner in the heel region may cause chafing or blisters due to movement of the foot in relation to the upper.

An important aspect of footwear design involves controlling the motion of the foot during activities that involve running. For many individuals, the motion of the foot while running proceeds as follows: The heel strikes the ground first, followed by the ball of the foot. As the heel leaves the ground, the foot rolls forward such that the toes make contact, and finally the entire foot leaves the ground to begin another cycle. During the time that the foot is in contact with the ground and rolling forward, it also rolls from the lateral side to the medial side, a process called pronation. That is, normally, the outside of the heel strikes first and the toes on the inside of the foot leave the ground last. While the foot is air borne and preparing for another cycle, the opposite process, called supination, occurs. Pronation is a normal and beneficial aspect of running, but may be a potential source of foot and leg injury, particularly if it is excessive.

Footwear designed for individuals with excessive pronation often incorporate pronation control devices to limit the degree of pronation during running. In general, pronation control devices are an additional element, such as a heel counter, or a modification of an existing

element, such as the sole structure. In general, a heel counter is a rigid member that extends around the heel portion of the footwear, thereby limiting movement of the heel. Additional support may be provided to a heel counter by including a bead of material, as disclosed in U.S. Patent Number 4,354,318 to Frederick, et al. Another prior art technique that enhances pronation control following foot impact involves building up the heel counter, as disclosed in U.S. Patent Numbers 4,255,877 to Bowerman and 4,287,675 to Norton, et al.

The sole structure may also be modified to control pronation. For example, the medial side of the sole structure may include higher density cushioning materials, as disclosed in U.S. Patent Numbers 4,364,188 to Turner, et al. and 4,364,189 to Bates. Similarly, a less compressible fluid chamber may be incorporated into the medial heel area of the sole structure, as disclosed in U.S. Patent Numbers 4,297,797 and 4,445,283, both to Meyers. Another prior art technique, as disclosed in U.S. Patent Number 5,247,742 to Kilgore, et al., involves incorporating a compression resistance increasing member into the midsole.

Although the prior art pronation control techniques exhibit a degree of success in controlling pronation, the techniques also add to the weight and manufacturing expense of footwear. The present invention was designed to cooperatively utilize a combination of structural features in a manner that effectively reduces the disadvantages of prior art sole structures.

### BRIEF SUMMARY OF THE INVENTION

The invention relates to an article of footwear that includes an upper for covering at least a portion of a foot of a wearer, a foot-supporting member that is removably-received by the upper, and a sole structure. The foot-supporting member is formed of a resilient material and has

a lower surface located opposite a foot-engaging surface. The lower surface is at a first elevation in a forefoot region of the foot-supporting member and the lower surface is at a second elevation in a heel region of the foot-supporting member, the second elevation being greater than the first elevation to define a recess below the heel region. The sole structure is attached to the upper and includes a midsole, a portion of the midsole forming an upward protrusion within the footwear that mates with the recess to support the heel region of the foot-supporting member.

In a first embodiment of the present invention, the footwear is configured for running. In order to reduce the rate at which the foot pronates, the foot-engaging surface is structured to have a downward cant in the medial-to-lateral direction and a region of reduced support generally underlying a fore portion of a first metatarsal and aft portions of a proximal hallux of the foot. The downward cant is located in the heel region but may extend throughout the length of the footwear. The region of reduced support may incorporate a material that has a greater compressibility than remaining portions of the foot-supporting member to facilitate plantarflexion. In addition to the downward cant and the region of reduced support, the footwear includes a region in the rear-lateral corner of the midsole that is more compressible than other portions of the midsole. The compressible region serves as a strikezone in the heel that limits pronation. The foot-engaging surface is also contoured to provide support for the foot. The contours include a heel depression, a medial arch support, and a depression underlying the fourth and fifth metatarsal heads. In addition, the heel region is generally raised in relation to the forefoot region.

In a second embodiment of the present invention, the footwear is configured for walking and includes a foot-supporting member that is contoured to provide support for the foot. In addition, the heel region is raised in relation to the forefoot region.

The various advantages and features of novelty that characterize the present invention are pointed out with particularity in the appended claims. To gain an improved understanding of the advantages and features of novelty that characterize the present invention, however, reference should be made to the descriptive matter and accompanying drawings which describe and illustrate various embodiments of the invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a lateral elevational view of an article of footwear in accordance with a first embodiment of the present invention.

FIG. 2 is a bottom plan view of the article of footwear depicted in FIG. 1.

FIG. 3A is a first partial cross-sectional view of the footwear, as defined by line 3A-3A in FIG. 2.

FIG. 3B is a second partial cross-sectional view of the footwear, as defined by line 3B-3B in FIG. 2.

FIG. 4 is a perspective view of a foot-supporting member of the footwear depicted in FIG. 1.

FIG. 5 is a lateral elevational view of the foot-supporting member depicted in FIG. 4.

FIG. 6 is a medial elevational view of the foot-supporting member depicted in FIG. 4.

FIG. 7 is a top plan view of the foot-supporting member depicted in FIG. 4.

FIGS. 8A to 8F are cross-sectional views of the foot-supporting member, as defined in FIG. 7.

FIG. 9 is a bottom plan view of the foot-supporting member depicted in FIG. 4.



FIG. 10 is a top plan view showing the spatial relationship between bones of a foot and the foot-supporting member depicted in FIG. 4.

FIG. 11 is a lateral elevational view of an article of footwear in accordance with a second embodiment of the present invention.

FIG. 12 is a partial cross-sectional lateral elevational view along a longitudinal centerline of the article of footwear depicted in FIG. 11.

FIG. 13 is a perspective view of a foot-supporting member of the footwear depicted in FIG. 11.

FIG. 14 is a lateral elevational view of the foot-supporting member depicted in FIG. 12.

FIG. 15 is a top plan view of the foot-supporting member depicted in FIG. 12.

#### DETAILED DESCRIPTION OF THE INVENTION

Referring to the figures, wherein like numerals indicate like elements, articles of athletic footwear in accordance with the present invention are illustrated. FIGS. 1-10 depict a first embodiment of the present invention, an article of footwear 100, which is a running shoe. FIGS. 11-15 depict a second embodiment of the present invention, an article of footwear 300, which is a walking shoe. The concepts disclosed in relation to footwear 100 and 300 may also be applied to other styles of footwear, including tennis shoes, basketball shoes, cross-training shoes, hiking boots, work boots, loafers, boat shoes, or dress shoes. Accordingly, footwear with a variety of intended uses, whether athletic or casual, are intended to fall within the scope of the present invention when coupled with the concepts disclosed herein.

The primary elements of footwear 100 are an upper 110, a sole structure 120 that is attached to upper 110, and a removable foot-supporting member 200. Footwear 100 is divided

into three regions: heel region 102, midfoot region 104, and forefoot region 106. Regions 102, 104, and 106 are not intended to demarcate precise areas. Rather, they are intended to define general areas to aid in discussion.

Upper 110 may be any conventional style of upper that performs functions related to the activities for which footwear 100 is designed, particularly running. Sole structure 120 includes a midsole 130 and an outsole 140. Midsole 130 may be formed of any conventional and resilient midsole material, including polyurethane foam and ethyl vinyl acetate, and extends from heel region 102 to forefoot region 106. As described below, however, the shock attenuating and energy absorbing characteristics of midsole 130 are primarily limited to heel region 102. Outsole 140 is attached to the lower surface of midsole 130 and provides a durable, ground-contacting surface. Foot supporting member 200 is located above midsole 130 and within the recess formed by upper 110. Depending upon the method by which footwear 100 is manufactured, a portion of upper 110 may extend between foot-supporting member 200 and midsole 130, as depicted in FIG. 3. Alternatively, foot-supporting member 200 may rest directly upon midsole 130.

The primary shock attenuating and energy absorbing element of conventional athletic footwear is an integral foam midsole that extends from the heel to the forefoot regions of the footwear. Conventional midsoles may also incorporate a fluid-filled bladder in accordance with the teachings of U.S. Patent Numbers 4,183,156, 4,219,945, 4,906,502, and 5,083,361, all issued to Rudy, and U.S. Patent Numbers 5,993,585 and 6,119,371, both issued to Goodwin, et al., and all hereby incorporated by reference. With regard to footwear 100, however, shock attenuation and energy absorption are divided among sole structure 120 and foot-supporting member 200. More particularly, sole structure 120 is configured such that midsole 130 provides shock



attenuation and energy absorption in heel region 102 and foot-supporting member 200 provides shock attenuation and energy absorption in forefoot region 106. With reference to FIG. 3, midsole 130 is depicted as extending from the back of heel region 102 to the front of forefoot region 106. In heel region 102, midsole 130 has a relatively great thickness, thereby imparting a significant degree of shock attenuation and energy absorption. Supplemental shock attenuation and energy absorption may be added to heel region 102 by incorporating a fluid-filled bladder into midsole 130. The thickness of midsole 130 decreases in midfoot region 104 and becomes relatively thin in the forefoot region 106. Accordingly, midsole 130 provides a relatively small degree of shock attenuation and energy absorption in forefoot region 106. Note that around the periphery of footwear 100 midsole 130 extends onto the sides of upper 110 to provide additional lateral and medial support to foot-supporting member 200.

Foot supporting member 200 includes a lower surface 210, an opposite foot-engaging surface 220, and a top cloth 230 attached to foot-engaging surface 220. Lower surface 210 is located in two general elevations that correspond with the contours formed on the upper surface of midsole 130. The area of lower surface 210 located in heel region 102 is, therefore, at a generally greater elevation than the area of lower surface 210 located in forefoot region 106. In midfoot region 104, the elevation of lower surface 210 transitions to the elevation of forefoot region 106. Accordingly, lower surface 210 is configured to define a recess in heel region 102 that mates with the upper surface of midsole 130, as depicted in FIG. 3. Foot-engaging surface 220 is located opposite lower surface 210 and is contoured to generally conform to the lower surface of a foot that is received by footwear 100. The area of foot-engaging surface 220 located in heel region 102 is generally at a greater elevation than the area located in forefoot region 106. The difference in elevation between the respective areas of foot-engaging surface 220, however,

is not as great as the difference between the areas of lower surface 210. Accordingly, the portion of foot-supporting member 200 located in forefoot region 106 has a greater thickness than the portion in heel region 102. The greater thickness in forefoot region 106 provides the primary means for shock attenuation and energy absorption in forefoot region 106. Top cloth 230 is attached to foot-engaging surface 220 and provides a comfortable area of contact for the foot. Other specific features of foot-engaging surface 220 will be discussed in greater detail below.

Detailed views of foot-supporting member 200 are depicted in FIGS. 4-9. Foot-engaging surface 220 is contoured to conform generally to the lower surface of a foot. The contours include a heel depression 222, an arch elevation 224, and a metatarsal head depression 226. Heel depression 222 generally corresponds with the area that makes contact with the heel of the wearer's foot. The indentation forming heel depression 222 receives the wearer's heel and seats the heel in relation to foot-engaging surface 220. Arch elevation 224, which is located on the medial side of midfoot region 104, provides support to the arch of the wearer's foot. Metatarsal head depression 226 is located in an area of foot-engaging surface 220 generally underlying the fourth and fifth metatarsal heads of a wearer's foot. A suitable material for foot-supporting member 200 includes phylon, a compression molded ethyl vinyl acetate, having a hardness of 53 to 58 degrees on the Asker C scale.

The elevation of foot-engaging surface 220 in heel region 102 is generally greater than the elevation in forefoot region 106, as discussed above. Foot-engaging surface 220 also includes a raised periphery in heel region 102 and midfoot region 104. The raised periphery provides a general depression extending across foot-engaging surface 220 that receives and secures the position of the foot. In alternative embodiments, the raised periphery may completely encircle foot-engaging surface 220.

Foot-engaging surface 220 also includes a downward cant extending from the medial side to the lateral side throughout the length of the foot-engaging surface 220, as depicted in FIGS. 8B, 8C, and 8D. A suitable angle for the downward cant is approximately three degrees, but may be in the range of one to four degrees. In alternative embodiments, the cant may be absent in areas of foot-engaging surface 220 located in forefoot region 106 or may be limited to heel region 102. The cant imparts pronation control by providing greater medial support, thereby lessening the tendency of the foot to rotate medially following heel strike. An advantage of forming the cant in foot-supporting member 200 is that midsole 130 may have a horizontal upper surface and upper 110 may extend vertically from midsole 130, thereby imparting increased stability.

A region of reduced support, represented in the figures by region 228, is located in the medial forefoot area of foot-engaging surface 220 and generally underlying a fore portion of a first metatarsal and an aft portion of a proximal hallux of the foot, as depicted in FIG. 10. During toe-off, the fore portion of the first metatarsal head tends to naturally extend below the plane of the remaining portions of the foot. Region 228 facilitates the downward movement of the first metatarsal head by incorporating a foam material under the first metatarsal and aft portion of the proximal hallux that is more compressible than the foam material under other portions of the foot. In forming foot-supporting member 220, a shallow depression corresponding with the area of region 228 is formed in foot-engaging surface 220. A material having greater compressibility than the primary portion of foot-supporting member 220 is then positioned in region 228 and secured through heat bonding or an adhesive, for example. The material forming region 228 may be the same as the foam forming foot-supporting member 200, but with a lower density to provide increased compliance. As discussed above, foot-supporting

member 200 may be primarily formed of phylon. A suitable material for region 228 is, therefore, a polyurethane foam material having a hardness that is approximately 10 degrees less on the Asker C scale than the phylon material forming remaining portions of foot-supporting member 200.

Conventional articles of footwear are manufactured on a last having the shape of the human foot. In general, the upper is formed around the last, thereby configuring a recess within the upper that has the general shape of the foot. A sole is then attached to the upper. With regard to footwear 100, however, the recess formed within upper 110 is configured to receive both the foot and foot-supporting member 200. Consequently, footwear 100 may be formed using a unique slip-lasting technique wherein the last has a lower surface that conforms to the shape of lower surface 210. According to this process, upper 110 is formed around the last and sole structure 120 is then attached to upper 110. Removal of the last from upper 110 forms a recess within footwear 100 that accommodates both the foot and foot-supporting member 200. Accordingly, foot-supporting member 200 is inserted into footwear 100 through the ankle opening. Foot-supporting member 200 is, therefore, removably-received by footwear 100. Alternatively, foot-supporting member 200 may be permanently secured within footwear 100.

The structure of footwear 100, particularly the removable nature of foot-supporting member 200, permits footwear 100 to be customized for a particular individual. Individuals with specific footwear needs may obtain replacement foot-supporting members 200 that conform to the specific needs of the individual. For example, an individual may require a foot-supporting member with a greater arch elevation or additional features that limit pronation. Furthermore, a foot-supporting member 200 may be custom manufactured to provide a physician-prescribed medical or therapeutic benefit.

member 200 may be primarily formed of phylon. A suitable material for region 228 is, therefore, a polyurethane foam material having a hardness that is approximately 10 degrees less on the Asker C scale than the phylon material forming remaining portions of foot-supporting member 200.

Conventional articles of footwear are manufactured on a last having the shape of the human foot. In general, the upper is formed around the last, thereby configuring a recess within the upper that has the general shape of the foot. A sole is then attached to the upper. With regard to footwear 100, however, the recess formed within upper 110 is configured to receive both the foot and foot-supporting member 200. Consequently, footwear 100 may be formed using a unique slip-lasting technique wherein the last has a lower surface that conforms to the shape of lower surface 210. According to this process, upper 110 is formed around the last and sole structure 120 is then attached to upper 110. Removal of the last from upper 110 forms a recess within footwear 100 that accommodates both the foot and foot-supporting member 200. Accordingly, foot-supporting member 200 is inserted into footwear 100 through the ankle opening. Foot-supporting member 200 is, therefore, removably-received by footwear 100. Alternatively, foot-supporting member 200 may be permanently secured within footwear 100.

The structure of footwear 100, particularly the removable nature of foot-supporting member 200, permits footwear 100 to be customized for a particular individual. Individuals with specific footwear needs may obtain replacement foot-supporting members 200 that conform to the specific needs of the individual. For example, an individual may require a foot-supporting member with a greater arch elevation or additional features that limit pronation. Furthermore, a foot-supporting member 200 may be custom manufactured to provide a physician-prescribed medical or therapeutic benefit.



An additional feature of footwear 100 relates to midsole 130. To reduce the rate at which the foot pronates, a portion 132 of midsole 130, which is located in the rear-lateral corner of heel region 102 has greater compressibility than other portions of midsole 130. As discussed in the Description of Background Art section, the outside of the heel, or the rear-lateral corner of the heel region, typically makes contact with the ground first. When the rear-lateral corner of footwear 100 contacts the ground, portion 132 compresses. As the foot rolls forward and to the medial side, the compressive force is transferred to the remaining portion of midsole 130. Because the remaining portion is less compressible than portion 132, the remaining portion resists the lateral-to-medial movement, thereby reducing the rate at which the foot pronates. To facilitate compression of the rear-lateral corner, outsole 140 is articulated, or divided into a first section 142 and a second section 144, as depicted in FIGS. 3A and 3B. First section 142 is located directly beneath portion 132 and second section 144 is located beneath the remainder of midsole 130. The area separating first section 142 from second section 144 defines a line of flexion along which midsole 130 flexes when the rear-lateral corner is compressed. A suitable material for midsole 130 is ethyl vinyl acetate having a hardness of 53 to 58 degrees on the Asker C scale. Portion 132 may be formed of a differing material, such as polyurethane having a hardness that is approximately 10 degrees less than the hardness of the ethyl vinyl acetate. The difference, however, may range between 5 and 15 degrees.

The rate at which the foot pronates is also limited by features incorporated into foot-supporting member 200. Heel depression 222, arch elevation 224, and metatarsal head depression 226 function to support the foot, particularly the arch of the foot, thereby permitting the natural structure of the foot to reduce pronation. In addition, foot-engaging surface includes the downward cant that extends from the medial side to the lateral side throughout the length of



the foot-engaging surface 220. The cant provides greater support on the medial side of footwear 100, thereby resisting pronation of the foot. Finally, region 228 permits the foot to achieve a natural positioning during toe-off in order to provide additional resistance to pronation.

Lower surface 210 may also include two fluid-filled bladders. A first bladder 212 may be located in heel region 102 and a second bladder 214 may be located in forefoot region 106. Second bladder 214 may include a first chamber 214a generally underlying joints between metatarsals and phalanges on a lateral side of the foot, a second chamber 214b generally underlying joints between metatarsals and phalanges on a medial side of the foot, and a third chamber 214c generally underlying a proximal hallux and a distal hallux of the foot. First chamber 214a and second chamber 214b may be connected by a conduit to place them in fluid communication. Similarly, second chamber 214b and third chamber 214c may be connected by a conduit to place them in fluid communication. A tensile member (not shown) may be disposed on the interior of each chamber to restrain outward movement of sheets that form second bladder 214. The tensile member may be of the type disclosed in U.S. Patent Numbers 4,906,502 and 5,083,361, both issued to Rudy, and U.S. Patent Numbers 5,993,585 and 6,119,371, both issued to Goodwin, et al. To provide additional support to the area surrounding second bladder 214 a cage 216 formed of a flexible material, such as ethyl vinyl acetate or a rubberized ethyl vinyl acetate, may be located around peripheral portions of second bladder 214.

Additional support for heel region 102 may be provided by a plate 218 located on lower surface 210. Plate 218 may have a u-shape that extends around heel region 102. Suitable materials for plate 218 include semi-rigid polymers or a composite material that combine glass or carbon fibers, for example, with a polymer.

Based upon the above discussion, footwear 100 is designed to be a lightweight running shoe that incorporates features for reducing the rate at which the foot pronates. Foot-supporting member 200 is removable and provides the option of interchanging a first foot-supporting member 200 with a second foot-supporting member 200 that has characteristics uniquely-suited to the individual. In addition, foot-supporting member may be custom manufactured for the individual and inserted into footwear 100.

Footwear 300, a walking shoe in accordance with the second embodiment of the present invention, is depicted in FIGS. 11-15 and includes an upper 310, a sole structure 320, and a foot-supporting member 330. Sole structure 320 is attached to upper 310 and configured to receive foot-supporting member 330. The primary elements of sole structure 320 include a midsole 322, a fluid-filled bladder 324 located in the heel portion of midsole 322, and an outsole 326. Midsole 322 may be formed of single material or multiple materials having differing properties. As depicted in FIG. 12, midsole 322 is formed of differing materials in the heel and forefoot portions. A suitable material for the heel portion is polyurethane having a hardness of 54 to 60 degrees on the Asker C scale. The forefoot portion may be formed from phylon having a hardness of 50 to 55 degrees on the Asker C scale. Foot-supporting member 330 may be formed of polyurethane, having a density of 0.35 grams per cubic centimeter and a hardness of 28 to 34 on the Asker C scale, and includes a lower surface 332 and a contoured foot-engaging surface 334. As with midsole 130 of footwear 100, midsole 322 is primarily located in the heel region such that foot supporting member 330 is configured to have a greater elevation in the heel region. For increased shock attenuation and energy absorption, lower surface 332 may incorporate a fluid-filled bladder 336 in the forefoot region. In addition, a similar fluid-filled bladder 338 may be incorporated into a portion of sole structure 320 located in the heel region, as

depicted in FIGS. 11 and 12. For ease of illustration, the interior of bladders 336 and 338 are illustrated without connections between the top and bottom surfaces. Conventional bladders with interior connections are preferably used, as disclosed in U.S. Patent Number 4,817,304 to Parker, et al, hereby incorporated by reference, and the aforementioned U.S. Patent Numbers 4,906,502 and 5,083,361 to Rudy.

A first advantage of footwear 300 over prior art footwear styles relates to the flexibility of sole structure 320. The laminar design of prior art sole structures limits overall flexibility. Sole structure 320, however, utilizes a separate foot-supporting member 330 in place of a conventional midsole in the forefoot. The separate design permits greater flexibility in the forefoot, particularly in the area corresponding with the joints between the metatarsals and phalanges of the wearer. A second advantage of footwear 300 relates to the thickness of foot-supporting member 330 in the heel region. As discussed in the Description of Background Art section, prior art sockliners with a relatively great thickness in the heel region had the potential to cause chafing and blisters due to movement of the foot in relation to the upper. This issue is resolved in footwear 300 by reducing the thickness of foot-supporting member 330 and increasing the thickness of midsole 322 in the heel region. Footwear 100 has a similar configuration and, therefore, benefits from these advantages.

The present invention is disclosed above and in the accompanying drawings with reference to a variety of embodiments. The purpose served by disclosure of the embodiments, however, is to provide an example of the various aspects embodied in the invention, not to limit the scope of the invention. One skilled in the art will recognize that numerous variations and modifications may be made to the embodiments without departing from the scope of the present invention, as defined by the appended claims.

## CLAIMS

That which is claimed is:

1. An article of footwear comprising:  
an upper for covering at least a portion of a foot of a wearer;  
a foot-supporting member that is removably-received by said upper, said foot-supporting member being formed of a resilient material and having a lower surface located opposite a foot-engaging surface, said lower surface being at a first elevation in a forefoot region of said foot-supporting member and said lower surface being at a second elevation in a heel region of said foot-supporting member, said second elevation being greater than said first elevation to define a recess below said heel region; and  
a sole structure attached to said upper, said sole structure including a midsole, a portion of said midsole forming an upward protrusion within said footwear that mates with said recess for supporting said heel region of said foot-supporting member.
2. The article of footwear of claim 1, wherein said foot-engaging surface includes a depression in said heel region for receiving a heel of the foot.
3. The article of footwear of claim 2, wherein said foot-engaging surface includes a depression in an area generally underlying fourth and fifth metatarsal heads of the foot.

4. The article of footwear of claim 3, wherein said foot-engaging surface includes a first elevated region in an area generally underlying a medial arch of the foot, said first elevated region supporting said medial arch.
5. The article of footwear of claim 4, wherein said foot-engaging surface includes a second elevated region in peripheral areas of said foot-engaging surface and in at least said heel region.
6. The article of footwear of claim 1, wherein said foot-supporting member incorporates a fluid-filled bladder in said forefoot region.
7. The article of footwear of claim 6, wherein said foot-supporting member incorporates a fluid-filled bladder in said heel region.
8. The article of footwear of claim 1, wherein said foot-supporting member includes a downward cant from a medial to a lateral side of said foot-engaging surface.
9. The article of footwear of claim 8, wherein said downward cant is located in said heel region and a portion of an midfoot region of said foot-supporting member.
10. The article of footwear of claim 8, wherein said downward cant is approximately three degrees.

11. The article of footwear of claim 1, wherein said foot-engaging surface includes a region of reduced support in a medial forefoot area, said foot-supporting member being substantially formed of a first material and said region of reduced support including a second material, said first material being less compressible than said second material.

12. The article of footwear of claim 11, wherein said region of reduced support is located adjacent a fore portion of a first metatarsal and an aft portion of a proximal hallux of the foot of the wearer.

13. The article of footwear of claim 1, wherein said foot-engaging surface includes a top cloth.

14. The article of footwear of claim 1, wherein said foot-engaging surface is at a third elevation in said forefoot region and said foot-engaging surface is at a fourth elevation at said heel region, said third elevation being less than said fourth elevation.

15. The article of footwear of claim 1, wherein said sole structure includes a first region and a second region, said first region being located in a rear-lateral corner of said sole structure and being more compressible than said second region.

16. The article of footwear of claim 15, wherein said sole structure includes an outsole having a first section that is attached to said first region and a second section that is attached to



said second region, said first section being separate from said second section to define a line of flexion in said sole structure.

17. The article of footwear of claim 1, wherein a heel plate is incorporated into said foot-supporting member in said heel region for providing support to said heel region.

18. An article of footwear, comprising:

an upper for covering at least a portion of a foot of a wearer;

a foot-supporting member that is removably-received by said upper, said foot-supporting

member being formed of a resilient material and having a foot-engaging surface

with a downward cant extending from a medial to a lateral side of said foot-

supporting member, and said foot-engaging surface including a region of reduced

support located in a medial forefoot area; and

a sole structure attached to said upper.

19. The article of footwear of claim 18, wherein said foot-engaging surface is contoured to include:

a depression in a heel region for receiving a heel of the foot;

a depression in an area generally underlying fourth and fifth metatarsal heads of the foot;

a first elevated region in an area generally underlying a medial arch of the foot; and

a second elevated region in peripheral areas of said foot-engaging surface and in at least

said heel region.

20. The article of footwear of claim 18, wherein said foot-supporting member includes a lower surface located opposite said foot-engaging surface, said lower surface being at a first elevation in a forefoot region of said foot-supporting member and said lower surface being at a second elevation in a heel region of said foot-supporting member, said first elevation being less than said second elevation to define a recess located under said heel region.
21. The article of footwear of claim 20, wherein said sole structure includes a midsole, a portion of said midsole forming an upward protrusion that mates with said recess for supporting said heel region of said foot-supporting member.
22. The article of footwear of claim 20, wherein said foot-engaging surface is at a third elevation in said forefoot region and said foot-engaging surface is at a fourth elevation in said heel region, said third elevation being less than said fourth elevation.
23. The article of footwear of claim 18, wherein said foot-supporting member is substantially formed of a first material and said region of reduced support includes a second material, said first material being less compressible than said second material.
24. The article of footwear of claim 18, wherein said region of reduced support is located adjacent a fore portion of a first metatarsal and an aft portion of a proximal hallux of the foot.
25. The article of footwear of claim 18, wherein said downward cant is located in a heel region and a portion of a midfoot region of said foot-supporting member.

26. The article of footwear of claim 18, wherein said downward cant is approximately three degrees.

27. The article of footwear of claim 18, wherein said sole structure includes a first region and a second region, said first region being located in a rear-lateral corner of said sole structure and being more compressible than said second region.

28. The article of footwear of claim 27, wherein said sole structure includes an outsole having a first section that is attached to said first region and a second section that is attached to said second region, said first section being separate from said second section to define a line of flexion in said sole structure.

29. The article of footwear of claim 18, wherein a heel plate is incorporated into a heel region of said foot-supporting member for providing support to said heel region.

30. An article of footwear comprising:

an upper for covering at least a portion of a foot of a wearer;

a foot-supporting member that is removably-received by said upper, said foot-supporting member being formed of a resilient material and having a lower surface located opposite a foot-engaging surface, said lower surface being at a first elevation in a forefoot region of said foot-supporting member and said lower surface being at a second elevation in a heel region of said foot-supporting member, said second

elevation being above said first elevation to define a recess below said heel region, and said foot-supporting member including a downward cant from a medial to a lateral side of said foot-engaging surface; and

a sole structure attached to said upper, said sole structure including a midsole, a portion of said midsole forming an upward protrusion within said footwear that mates with said recess for supporting said heel region of said foot-supporting member, and said sole structure including a first region and a second region, said first region being located in a rear-lateral corner of said sole structure and being more compressible than said second region.

31. The article of footwear of claim 30, wherein said foot-engaging surface includes a depression in said heel region for receiving a heel of the foot.

32. The article of footwear of claim 31, wherein said foot-engaging surface includes a depression in an area generally underlying fourth and fifth metatarsal heads of the foot.

33. The article of footwear of claim 32, wherein said foot-engaging surface includes a first elevated region in an area generally underlying a medial arch of the foot, said first elevated region supporting said medial arch.

34. The article of footwear of claim 33, wherein said foot-engaging surface includes a second elevated region in peripheral areas of said foot-engaging surface and in at least said heel region.

35. The article of footwear of claim 30, wherein said foot-supporting member incorporates a fluid-filled bladder in said forefoot region.
36. The article of footwear of claim 35, wherein said foot-supporting member incorporates a fluid-filled bladder in said heel region.
37. The article of footwear of claim 30, wherein said downward cant is located in said heel region and a portion of a midfoot region of said foot-supporting member.
38. The article of footwear of claim 30, wherein said downward cant is approximately three degrees.
39. The article of footwear of claim 30, wherein said foot-engaging surface includes a region of reduced support in a medial forefoot area, said foot-supporting member being substantially formed of a first material and said region of reduced support including a second material, said first material being less compressible than said second material.
40. The article of footwear of claim 39, wherein said region of reduced support is located adjacent a fore portion of a first metatarsal and an aft portion of a proximal hallux of the foot of the wearer.
41. The article of footwear of claim 30, wherein said foot-engaging surface includes a top cloth.

42. The article of footwear of claim 30, wherein said foot-engaging surface is at a third elevation in said forefoot region and said foot-engaging surface is at a fourth elevation at said heel region, said third elevation being less than said fourth elevation.

43. The article of footwear of claim 30, wherein said sole structure includes an outsole having a first section that is attached to said first region and a second section that is attached to said second region, said first section being separate from said second section to define a line of flexion in said sole structure.

44. The article of footwear of claim 30, wherein a heel plate is incorporated into said foot-supporting member in said heel region for providing support to said heel region.

45. An article of footwear comprising:

an upper for covering at least a portion of a foot of a wearer;

a foot-supporting member that is removably-received by said upper, said foot-supporting member being formed of a shock attenuating and energy absorbing material and having:

a lower surface located at a first elevation in a forefoot region of said foot-supporting member and at a second elevation in a heel region of said foot-supporting member, said first elevation being less than said second elevation to define a recess below said heel region,



a foot-engaging surface located opposite said lower surface, said foot-engaging surface being at a third elevation in said forefoot region and at a fourth elevation at said heel region, said third elevation being less than said fourth elevation,

a downward cant extending from a medial to a lateral side of said foot-engaging surface, and

a region of reduced support in a medial forefoot area of said foot-engaging surface, said foot-supporting member being substantially formed of a first material and said region of reduced support including a second material, said first material being less compressible than said second material; and

a sole structure attached to said upper, said sole structure including a midsole, a portion of said midsole forming an upward protrusion within said footwear that mates with said recess for supporting said heel region of said foot-supporting member, and said sole structure including a first region and a second region, said first region being located in a rear-lateral corner of said sole structure and being more compressible than said second region.

46. The article of footwear of claim 45, wherein said foot-engaging surface includes a depression in said heel region for receiving a heel of the foot.

47. The article of footwear of claim 45, wherein said foot-engaging surface includes a depression in an area generally underlying fourth and fifth metatarsal heads of the foot.

48. The article of footwear of claim 47, wherein said foot-engaging surface includes a first elevated region in an area generally underlying a medial arch of the foot, said first elevated region supporting said medial arch.

49. The article of footwear of claim 48, wherein said foot-engaging surface includes a second elevated region in peripheral areas of said foot-engaging surface and in at least said heel region.

50. The article of footwear of claim 45, wherein said foot-supporting member incorporates a fluid-filled bladder in said forefoot region.

51. The article of footwear of claim 50, wherein said fluid-filled bladder includes a first chamber generally underlying joints between metatarsals and phalanges on a lateral side of the foot, a second chamber generally underlying joints between metatarsals and phalanges on a medial side of the foot, and a third chamber generally underlying a proximal hallux and a distal hallux of the foot, said first chamber and said second chamber being in fluid communication, and said second chamber and said third chamber being in fluid communication.

52. The article of footwear of claim 50, wherein said foot-supporting member incorporates a fluid-filled bladder in said heel region.

53. The article of footwear of claim 45, wherein said downward cant is located in said heel region and a portion of a midfoot region of said foot-supporting member.

54. The article of footwear of claim 45, wherein said downward cant is approximately three degrees.
55. The article of footwear of claim 45, wherein said region of reduced support is located adjacent a fore portion of a first metatarsal and an aft portion of a proximal hallux of the foot of the wearer.
56. The article of footwear of claim 45, wherein said foot-engaging surface includes a top cloth.
57. The article of footwear of claim 45, wherein said sole structure includes an outsole having a first section that is attached to said first region and a second section that is attached to said second region, said first section being separate from said second section to define a line of flexion in said sole structure.
58. The article of footwear of claim 45, wherein a heel plate is incorporated into said foot-supporting member in said heel region for providing support to said heel region.






FIG. 3B




FIG. 9





FIG. 10








FIG. 8A





FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E







FIG. 8F








FIG. 14




FIG. 15

